

EcoBoard White Duo

Chipboard with wood-free, white offset paper on both sides



GRAMMAGE	THICKNESS	BULK
g/m ²	µm	cm ³ /g
500	700	1.40
600	800	1.33
700	900	1.29
800	1000	1.25
900	1200	1.33
1000	1450	1.45
1100	1600	1.46
1200	1550	1.29
1300	1700	1.31
1400	1850	1.32
1500	2000	1.33
1600	2150	1.34
1700	2250	1.32
1800	2400	1.33
1900	2550	1.34
2000	2700	1.35
2310	3000	1.30



APPLICATIONS

Graphics • POS displays • folding cartons

PRINTING

Offset printing • flexographic printing • screen printing

CONVERSION

UV, water-based and conventional varnish • foil and film lamination • hot foil stamping and cold foil transfer • embossing (high, relief, structure, micro) • die cutting, creasing, grooving, perforating, flock coating

ADDITIONAL INFORMATION

www.kapag.com

Tolerances / Testing Standards

Grammage (DIN ISO 536) ± 5%
 Thickness (DIN EN 20534) ± 5%
 Bulk ± 5%
 Stiffness (DIN 53121).....
 Brightness (ISO 2470) ± 2 Elrepho (front and reverse side)
 Opacity (ISO 2471)
 Roughness (ISO 8791/4)

Printing Surface Properties

ISO Brightness (front and reverse side)..... 103%
 Roughness
 Opacity



The mark of responsible forestry
 FSC® C058892