

# EcoKraft

Kraftliner with brown, white or coloured front and back layer



GRAMMAGE	THICKNESS	BULK
g/m <sup>2</sup>	µm	cm <sup>3</sup> /g
200	270	1.35
300	405	1.35
400	540	1.35
600	810	1.35
800	1080	1.35
960	1310	1.36



EcoKraft is also available one side coated (GC), both sides coated (GC Duo) or coloured on both sides (Colour Duo).

## APPLICATIONS

Packaging • Folders • Envelopes

## PRINTING

Screen printing • flexographic printing

## CONVERSION

Die-cutting, creasing; to a certain degree suitable for grooving

## ADDITION INFORMATION

[www.kapag.com](http://www.kapag.com)

### Tolerances / Testing Standards

Grammage (DIN ISO 536) ..... ± 5%  
 Thickness (DIN EN 20534) ..... ± 5%  
 Bulk ..... ± 5%  
 Stiffness (DIN 53121).....  
 Brightness (ISO 2470) .....  
 Opacity (ISO 2471) .....  
 Smoothness (ISO 8791/4) .....

### Printing Surface Properties

ISO Brightness [coated side(s)].....  
 Smoothness (PPS).....  
 Opacity .....



The mark of responsible forestry  
 FSC® C058892